



Construction Metal Forming


# MetClad® D33

## TRAPEZOIDAL CLADDING PROFILE ROOF - REVERSE - STEEL GRADE S220

MetClad® D33 has exceptional spanning capabilities. The result – a highly cost-effective, attractive, and easy-to-install cladding solution.



### REVERSE: AVAILABLE WITH OR WITHOUT SWAGES



	Span [m]	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0	2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.0	
		Gravity	Single	4.15	3.69	3.32	2.89	2.43	2.07	1.78	1.46	1.20	1.00	0.85	0.72	0.62	0.53	0.46	0.41	0.36	0.32	0.28	0.25	0.22	0.20
	Double	2.68	2.28	1.97	1.72	1.52	1.35	1.21	1.09	0.99	0.90	0.82	0.76	0.70	0.65	0.60	0.56	0.52	0.49	0.46	0.42	0.37	0.34	0.30	
	Multi	3.14	2.68	2.32	2.03	1.80	1.60	1.44	1.30	1.18	1.08	0.99	0.91	0.84	0.78	0.72	0.67	0.59	0.53	0.47	0.42	0.37	0.34	0.30	
0.5mm	Uplift	Single	4.15	3.69	3.32	3.02	2.68	2.28	1.97	1.71	1.51	1.33	1.19	1.07	0.96	0.87	0.80	0.72	0.63	0.56	0.50	0.44	0.40	0.36	0.32
	Double	2.58	2.19	1.89	1.64	1.45	1.29	1.15	1.03	0.94	0.85	0.78	0.72	0.66	0.61	0.57	0.53	0.49	0.46	0.43	0.40	0.38	0.36	0.34	
	Multi	3.04	2.59	2.23	1.95	1.72	1.53	1.37	1.24	1.12	1.02	0.93	0.86	0.79	0.73	0.68	0.63	0.59	0.55	0.52	0.49	0.46	0.43	0.41	
0.7mm	Gravity	Single	8.20	6.48	5.25	4.34	3.64	3.10	2.68	2.23	1.84	1.54	1.29	1.10	0.94	0.81	0.71	0.62	0.55	0.48	0.43	0.38	0.34	0.31	0.28
	Double	4.85	4.10	3.52	3.06	2.68	2.38	2.12	1.90	1.72	1.56	1.43	1.31	1.20	1.11	1.03	0.95	0.89	0.80	0.72	0.64	0.57	0.52	0.47	
	Multi	5.73	4.86	4.18	3.64	3.20	2.84	2.54	2.28	2.06	1.88	1.71	1.57	1.45	1.34	1.18	1.03	0.91	0.80	0.72	0.64	0.57	0.52	0.47	
0.9mm	Uplift	Single	8.24	7.32	6.05	5.00	4.20	3.58	3.09	2.69	2.36	2.09	1.87	1.68	1.51	1.37	1.23	1.07	0.95	0.84	0.74	0.66	0.60	0.54	0.48
	Double	4.57	3.84	3.29	2.85	2.49	2.20	1.96	1.75	1.58	1.43	1.30	1.19	1.09	1.01	0.93	0.87	0.80	0.75	0.70	0.66	0.62	0.58	0.55	
	Multi	5.41	4.57	3.91	3.40	2.98	2.63	2.35	2.11	1.90	1.73	1.57	1.44	1.32	1.22	1.13	1.05	0.98	0.91	0.85	0.80	0.75	0.71	0.67	
1.2mm	Gravity	Single	11.03	8.72	7.06	5.83	4.90	4.18	3.60	3.06	2.52	2.10	1.77	1.51	1.29	1.11	0.97	0.85	0.75	0.66	0.59	0.52	0.47	0.42	0.38
	Double	7.21	6.05	5.16	4.46	3.89	3.43	3.05	2.73	2.46	2.22	2.02	1.85	1.69	1.56	1.44	1.34	1.24	1.10	0.98	0.87	0.78	0.71	0.64	
	Multi	8.56	7.21	6.16	5.33	4.67	4.12	3.67	3.29	2.96	2.68	2.44	2.24	2.05	1.86	1.62	1.41	1.24	1.10	0.98	0.87	0.78	0.71	0.64	
1.2mm	Uplift	Single	12.32	9.73	7.88	6.51	5.47	4.66	4.02	3.50	3.08	2.73	2.43	2.18	1.97	1.79	1.60	1.40	1.23	1.09	0.97	0.87	0.78	0.70	0.63
	Double	6.84	5.72	4.87	4.19	3.65	3.21	2.85	2.54	2.29	2.07	1.88	1.71	1.57	1.44	1.33	1.23	1.14	1.07	0.99	0.93	0.87	0.82	0.77	
	Multi	8.14	6.83	5.82	5.03	4.39	3.87	3.43	3.07	2.76	2.50	2.27	2.08	1.91	1.75	1.62	1.50	1.39	1.30	1.21	1.14	1.07	1.00	0.94	

- Available in 0.5mm, 0.7mm, 0.9mm and 1.2mm gauges.
- Tables calculated by the SCI to BS EN 1993-1-3:2006.
- All loads are unfactored / characteristic and in kN/m<sup>2</sup>. Load factor (working loads to ultimate) x 1.5.
- Deflection Limits: Gravity Load Case = Span / 200, Wind Uplift Load Case = Span / 150.
- Cladding profile available in various finishes and colours. Contact CMF for more information.



For further information please contact CMF:

March 2024: v1.4



Construction Metal Forming

Unit 3, Mamhilad Technology Park,  
Old Abergavenny Rd, Mamhilad,  
Monmouthshire, NP4 0JJ.

Customer services: 01495 761 080

Sales enquiries: 01495 788 936

Technical support: 01495 788 937

e: info@cmf.uk.com | www.cmf.uk.com